

OPTIONS FOR DSTV VIEWERS

Multichoice DSTV viewers in Southern Africa who wish to continue watching Hope Channel are requested to consider the following options.

Please choose your group below:

Group 1: If you have **older** standard models (660 to 990) - [Click here](#)

[Instructions for older models \(DSD 660 to 990, Dual View etc.\) - Click here](#)

[Instructions for newer model 3U - Click here](#)

OPTIONS FOR INSTALLING FTA RECEIVERS

ALONGSIDE DSTV DECODERS

Group 2: If you have **later** standa

FOR NON-PVR DECODERS

Such as DSD 1110, 1131 and later

You will need to install [Free-to-Air receiver](#) alongside your DSTV decoder

Option 1: (No extra cable needed)

Install a splitter (or T-piece) on the incoming cable from the dish, with one coax cable going to the FTA

Option 2: (Extra cable needed)

Replace the **Single LNBF** with a **Twin LNBF**
Bring an extra RG-6 cable down for the Receiver.

{This option enables you to take the new cable to a different room for viewing Hope Channel }

Group 3: If you have DSTV **PVR or HD** models

FOR PVR DECODERS

You will need to install [Free-to-Air receiver](#) alongside your DSTV decoder

Option 1: (Extra cable needed)

Replace the **Twin LNBF** with a **Quad-LNBF** on your
with an extra RG-6 cable for the Receiver.

{This option enables you to take the new cable to a different room for viewing Hope Channel }

Option 2: (No extra cable needed) - Very suitable for PVR models

Change the **Twin LNBF** on your current dish to **SATCR-LNB** with 1
Y ou will need a 2 Legacy port unit if you have an Extra-View decoder.
One of the legacy ports is for the Extra-View decoder, and the other for the FTA receiver.
Remove the 4 or 6-way multi-switch if there is one fitted.

If you are given a single **Universal Type** that the Legacy port is a
Establish whether it is a 10600MHz High Band.

If it is a 10700MHz High Band then the LNB settings should be changed.

Connect the one cable to **SAT** terminal on the LNBF.

Connect the other end to **SAT-CR** input on the PVR.

The DSTV decoder must be reset for the SAT-CR LNBF as follows :-

Press **" MENU "** and go to **"Advanced Options"** , then p
Enter PIN **" 9 9 4 9 "** and move down to **"LNB Mode"** (current
Change it to **"SAT-CR Univ"** . Press **"OK"** to save
Then press the **Yellow** Button to **"Scan all enabled networks"**
The Decoder will bring in all the channels after the scan.
The one **Legacy** port gets connected to the **FTA** Receiver

[Acknowledgement with thanks - Mr Ivor Cartmell]

A further option for all groups:....

INTERNET VIEWING

Go to www.hopetv.org and click on the channel you require

If you need to talk to someone about these options,
please contact our Help [line@hopetv.org](mailto:help@hopetv.org) (SA) 0860-467-388 or email:

[You may want to print this page for your Installer]